


# FP6060C040-1

## Flat Panel LED Lighting




- Low profile LED Panel light
- Recessed, Pendant or wall mount
- Proven high quality LED's

Length x Width x Height	595 x 595 x 9mm
Trim	Aluminium
Weight	3.68Kg

- **Ultra Low Power Consumption:**  
Reduced Energy Bills
- **Instant Start:**  
No warm up time needed
- **Low Heat:**  
Reduction in air-conditioning running costs
- **No Mercury Lamps:**  
No specialist waste management required





Hanging



Recessed



Mounted



Model Name / Part Number	Flat Panel: FP6060C040-1	
Power Rating – Panel Only	40 Watts	
Typical Lumen output	2900 lms	
Total circuit watts when used with recommended power supply	37 Watts	
Lumens per circuit watt	78 lms/Watt	
Colour Temperature	6000 K	
CRI	80 +	
Uniformity	80% +	
Power Factor when used with recommended Power Supply	0.9 +	
Supporting Surface material	AL	
Panel Class - Panel Only-	Class III	
IP Rating - Panel Only-	IP20	
Typical ambient operating Temperature	25°C	
Maximum operating temperature - Panel Only-	50°C	
Lifetime - L70	40'000 Hours	
DC Rated input voltage /Current - Panel Only-	24-36 V / DC 1200mA	
Power supply and control options	Non Dimmable: PCS045-120-1	Dimmable: PCM045-120-1
Accessories	Hanging Kit: ACH002-CSC-1	Emergency Kit: Optional



IP20

