

## DH351

High resolution presentations









- Bright 3,600 lumens with 22,000:1 contrast ratio
- Full HD 1080p resolution
- HDMI-Link support simplifies control of connected HDMI devices and video sources
- Outstanding lamp life up to 15,000 hours (Dynamic) reduces overall cost of ownership.

Project bright Full HD 1080p content with the DH351. The excellent color reproduction and high-quality 22,000:1 contrast ratio ensures incredible images up to 301-inches so every presentation is stunning and visible by everyone in the room.



## **Specifications**

Remote control

Speaker count Watts per speaker

Optional wireless models

Power consumption (min)

Power consumption (max)
Weight and dimensions

Dimensions (W x D x H) Gross weight

In the box

Power

(standby)

Net weight

Power supply Power consumption

Display/image DIPTM Display technology Resolution 1080p Full HD (1920x1080) Brightness 3,600 lumens Contrast ratio 22,000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3 Keystone correction -+/-40° vertical Uniformity 80% Screen size 28" ~ 301" diagonal Lamp info Light source type Lamp Lamp watts 240 4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to) Optical Throw ratio 1.47:1 ~ 1.62:1 39.37" - 385.83" Projection distance Zoom 1.1 Zoom type Manua Focal length (mm) 15.59mm~17.14mm/0.614"~0.675" Native offset Connectivity Connections Inputs 1 x HDMI 1.4a 3D support Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A General Noise level (typical) 26dB Noise level (max) 28dB PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 2D compatibility 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Security Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, OSD / display languages Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max Operating conditions humidity 85%

Backlit home remote

HDCast Pro, WHD200

100 ~ 240V, 50 ~ 60Hz

12.44" x 9.61" x 4.25"

AC power cord Remote control 2x AAA batteries Basic user manual

5W

0.5W

205W 295W

8.4 lbs 6.17 lbs



