

ML1050ST+

Ultra-compact short throw LED projector





- HD Ready and LED technology Great for movies, gaming and PC-free presentations
- Short throw lens with auto focus
- Feature packed Built in media player, optional wireless, HDMI, MHL, micoSD and built in speaker,
- Ultra compact and lightweight only 420g

Building on the successful ML1050ST the all new ML1050ST+ has all the benefits with the addition of auto focus for a seamless setup.

Perfect for meetings, presentations or movies on-the-go. This tiny projector weighs just 420g and comes with a convenient carry bag.



Specifications

Dimensions (W x D x H) mm

Gross weight

Net weight

EAN: 5055387662278, Colour: V	Vhite
Display/image	
Display technology	DLP™
Resolution	WXGA (1280x800)
Brightness (HK/ANSI)	1000/500
Contrast ratio	20,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15.375 ~ 91.146Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	90%
Screen size	1.27m ~ 2.54m (50" ~ 100") diagonal
Lamp info	
Light source type	LED
LED life	20,000 hours
Optical	
Throw ratio	0.8:1
Projection distance (m)	0.86m - 1.72m
Zoom type	Fixed
Focal length (mm)	8.02mm/0.32"
Native offset	100%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x microSD card, 1 x USB-A reader, 1 x Universal I/O - VGA
	Outputs 1 x Audio 3.5mm
General	
Noise level (min)	22dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz)
3D compatibility	SVGA 120Hz, XGA 120Hz
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	12 languages: Dutch, English, French, German, Greek, Italian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C~35°C/41°F~95°F, max altitude 2500M/8202.5ft, max humidity 85%
Remote control	Card style
Speaker count	1
Watts per speaker	1W
In the box	Carry bag
	Universal I/O cable
	AC power cord
	Remote control Battery
	Basic user manual
Operating system	Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS
compatibility	8+
Input lag	16.00ms
Optional wireless models	WUSB
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (max)	77W
Weight and dimensions	
Dimensions (W x D x H) mm	112 x 123 x 57

112 x 123 x 57

0.42 kg

1.2 kg



•••
(•) (*) (•)
Optoma



Copyright © 2024, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 14032024122941