


X330UST

Ultra Short Throw Projector



- **Bright XGA projector - 3600 ANSI Lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **Ultimate Control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - 2x HDMI and built-in 16W speaker**

The X330UST, is perfect for businesses, schools and colleges. It is bright with an ultra short throw meaning it can project a 100" image from less than 0.5m away. And having the projector installed so close to the wall avoids any shadows being cast across the screen from the presenter(s).

It provides a complete package for engaging learning with many new features, including two HDMI inputs, powered USB port, native office viewer and powerful 16W built-in speaker.



Specifications

| | |
|----------------------------------|--|
| Display/image | |
| Display technology | DLP |
| Resolution | XGA (1024x768) |
| Brightness | 3,600 lumens |
| Contrast ratio | 20,000:1 |
| Native aspect ratio | 4:3 |
| Aspect ratio - compatible | 16:9 |
| Keystone correction - horizontal | +/-4° |
| Keystone correction - vertical | +/-4° |
| Horizontal scan rate | 15.375 ~ 91.147Khz |
| Vertical scan rate | 24 ~ 85(120 for 3D)Hz |
| Uniformity | 80% |
| Screen size | 1.78m ~ 2.54m (70" ~ 100") diagonal |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 240 |
| Lamp life (hours) | 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) |
| Optical | |
| Throw ratio | 0.33:1 |
| Projection distance (m) | 0.47m - 0.68m |
| Zoom type | Fixed |
| Focal length (mm) | 3.72 |
| Native offset | 120% |
| Connectivity | |
| Connections | Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 2 x USB-A reader/wireless Outputs 1 x VGA, 1 x Audio 3.5mm Control 1 x RS232, 1 x RJ45 |
| General | |
| Noise level (typical) | 26dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Data remote with laser and mouse function |
| Speaker count | 1 |
| Watts per speaker | 16W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | QuickCast Bundle, QuickCast starter kit, WHD200, WUSB |
| Networking | |
| LAN - control | Yes |
| LAN - display | Yes |
| LAN - wireless networking | Yes - optional |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 200W |
| Power consumption (max) | 275W |
| Weight and dimensions | |
| Net weight | 3.9kg |
| Dimensions (W x D x H) mm | 343 x 383 x 112 |

