H185X Bright HD Ready home entertainment projection







- Lights on viewing 3700 ANSI lumens
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project any time of day using this bright, portable HD Ready projector. Perfect for watching live sports, TV shows and movies or playing the latest action-packed games on a huge screen.



Easy to setup and use with a built-in speaker and HDMI input. Perfect for connecting a laptop, PC, Blu-ray player, media streamer or games console. You can even take it round to a friend's house for a sports event, movie night or games marathon with the optional carry bag.

Specifications

EAN: 5055387664838, Colour: Black	
Display/image	
Display technology	DLPTM
Resolution	WXGA (1280x800)
Brightness	3,700 lumens
Contrast ratio	28.000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	
	0.82m ~ 7.61m (32.24" ~ 299.53") diagonal
Lamp info Light source type	Lamp
0 11	
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical Throw ratio	1 55.1 1 70.1
	1.55:1 ~ 1.73:1
Projection distance (m)	1m - 12m
Zoom	1.1 Manual
Zoom type	Manual
Focal length (mm)	21.85 ~ 24
Native offset	112%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1
	x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
General	
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
25	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
	Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
Operating conditions	Turkish, Vietnamese
operating conditions	Iurkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control Speaker count	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style
Remote control Speaker count Watts per speaker	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1
Remote control Speaker count Watts per speaker	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control
Remote control Speaker count Watts per speaker	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery
Remote control Speaker count Watts per speaker In the box	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual
Remote control Speaker count Watts per speaker In the box Optional wireless models	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery
Remote control Speaker count Watts per speaker In the box Optional wireless models Power	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby)	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W 225W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W
Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm Gross weight Net weight	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Card style 1 10W AC power cord Remote control Battery Basic user manual WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 187W 225W







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 18082023044541