

UHD38

Bright 4K UHD gaming and home entertainment projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 4000 lumens for use any time of day
- Lightning fast gaming projector Delivers 1080p 240Hz with an ultra-low input lag of 4.2ms
- Full 3D compatible Experience life-like bigscreen entertainment



Immerse yourself in a world of Ultra HD gaming, live sports and TV shows. The UHD38 delivers impressive bright 4K UHD quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz - perfect for a competitive gaming advantage.

Packed with the latest technology and features, this stylish projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D and two HDMI 2.0 ports. Perfect for enjoying life-like big-screen entertainment in any living space.

Specifications

EAN: 5055387665378, Colour: White

Display/image DLP™ Display technology Resolution UHD (3840x2160) 4,000 lumens Brightness Contrast ratio 1,000,000:1 Native aspect ratio 16.9 Aspect ratio - compatible 4:3 +/-40° Keystone correction horizontal Keystone correction - vertical +/-40° Horizontal scan rate 31 ~ 135Khz 24 ~ 120Hz Vertical scan rate 80% Uniformity

Screen size 0.84m ~ 7.62m (33" ~ 300") diagonal

Lamp info
Light source type
Lamp watts 240

Lamp life hours (up to) 4000 (Bright), 15000 (Dynamic), 10000 (Eco)

 Optical
 1.5:1 ~ 1.66:1

 Projection distance (m)
 1.21m − 9.9m

 Zoom
 1.1

 Zoom type
 Manual

Focal length (mm) 15.84 mm~17.42mm/0.624"~0.686"

 Lens shift
 Vertical +0%

 Native offset
 105%

Connectivity

Connections Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio

Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power

1.5A

Control 1 x RS232, 1 x 12V trigger

 General
 26dB

 Noise level (typical)
 26dB

 Noise level (max)
 28dB

PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,

SVGA, VGA, Mac

2D compatibility 4801/p, 5761/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)

3D compatibility Frame-pack: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%

Remote control Backlit home remote

 Speaker count
 1

 Watts per speaker
 10W

 In the box
 AC power cord

 Remote control
 Remote control

Remote control 2x AAA batteries Basic user manual

Input lag 4.20ms
Power

Power supply 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 220W

 Power consumption (max)
 305W

Weight and dimensions

 Dimensions (W x D x H) mm
 315 x 270 x 118

 Gross weight
 4.68 kg

 Net weight
 3.98 kg





