







- Bright 1080p projector 3600 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Beam bright, eye catching content with the Full HD 1080p DH334 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including HDMI, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.



Specifications

Specifications	
Display/image	
Display technology	
Resolution	1080p Full HD (1920x1080)
Brightness	3,600 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	70% 0.71 m - 7.05 m (00" - 001") d'accerd
Screen size	0.71m ~ 7.65m (28" ~ 301") diagonal
Lamp info	Lown
Light source type	Lamp
Lamp watts	240 4000 (Bright) 12000 (Duramia) 10000 (Eac) 15000 (Eacu)
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical Throw ratio	1 47.1 1 69.1
Throw ratio Projection distance (m)	1.47:1 ~ 1.62:1
Projection distance (m)	1m - 9.8m
Zoom Zoom tuno	1.1 Monucl
Zoom type Focal length (mm)	Manual 15.59 ~ 17.14
Native offset	13.59 ~ 17.14 116%
Connectivity	11070
Connections	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
	Control 1 × 1102.02
General	
Noise level (typical)	27dB
Noise level (max)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080/50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
1 0	Card style
	Gard Style
Remote control	1
Remote control Speaker count	
Remote control Speaker count Watts per speaker	1 10W AC power cord, remote control, Battery, basic user manual
Remote control Speaker count Watts per speaker In the box	1 10W
Remote control Speaker count Watts per speaker In the box Optional wireless models	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit,
Remote control Speaker count Watts per speaker In the box Optional wireless models Power	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit,
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power Power consumption (standby) Power consumption (min)	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200 100 ~ 240V, 50 ~ 60Hz
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power Power supply Power consumption (standby)	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min)	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W
Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	1 10W AC power cord, remote control, Battery, basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W 295W



B () (30) Keystone-
() () () () () () () () () () () () () (
Optomo



Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 23082023091606