

W335e

Bright projection









- Bright WXGA projector 3800 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W335e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



Specifications

Weight and dimensions Dimensions (W x D x H)

Gross weight

Net weight

Specifications	
Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	3.800 lumens
Contrast ratio	22.000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction -	+/-40°
vertical	+/-40
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.82m ~ 7.61m (32.24" ~ 299.53") diagonal
	0.02111 = 7.01111 (02.24 = 233.30) diagonal
Light source type	Lomp
Lamp watts	Lamp 203
•	
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	1.55.4 1.70.4
Throw ratio	1.55:1 ~ 1.73:1
Projection distance (m)	1m - 12m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24
Native offset	112%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),
	1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
General	
Noise level (typical)	Control 1 x RS232
Noise level (typical) Noise level (max)	Control 1 x RS232 27dB
Noise level (typical) Noise level (max) PC compatibility	Control 1 x RS232 27dB 29dB
Noise level (typical) Noise level (max) PC compatibility	Control 1 x RS232 27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Noise level (typical) Noise level (max) PC compatibility	Control 1 x RS232 27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85%
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K/1L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480l/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit,
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MVJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480I/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power Power supply	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480I/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Optional wireless models Power Power Supply Power consumption	27dB 29dB FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC MJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) 3D ready Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Card style 1 10W AC power cord Remote control Battery Basic user manual HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200

316 x 244 x 108

4.4 kg

3 kg



