

H184X Bright HD ready home entertainment projection





- Lights on viewing 3600 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project any time of day using this bright, portable compact projector. Designed for watching TV shows, sports and movies or playing the latest action-packed games on a huge screen. This is your perfect HD ready home entertainment projector.



Specifications

Display/image	
Display technology	DLP™ MXCA (1280×800)
Resolution	WXGA (1280x800)
Brightness	3,600 lumens
Contrast ratio	28,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
lorizontal scan rate	15.38 ~ 91.15Khz
/ertical scan rate	50 ~ 85(120 for 3D)Hz
Jniformity	75%
Screen size	32.24" ~ 299.53" diagonal
Lamp info	
_ight source type	Lamp
_amp watts	203
_amp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.55:1 ~ 1.73:1
Projection distance	39.37" - 472.44"
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85mm~24mm/0.86"~0.945"
lative offset	112%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A Control 1 x RS232
General	
loise level (typical)	27dB
loise level (max)	29dB
C compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
	humidity 85%
Remote control	Card style
speaker count	1
Vatts per speaker	10W
n the box	AC power cord Remote control Battery
	Basic user manual
	WHD200
ptional wireless models	
ower	100 ~ 240V, 50 ~ 60Hz
Dptional wireless models Power Power supply Power consumption standby)	100 ~ 240V, 50 ~ 60Hz 0.5W
Power Power supply Power consumption standby)	
Power Power supply Power consumption	0.5W
Power Power supply Power consumption standby) Power consumption (min)	0.5W 187W
Power Power supply Power consumption standby) Power consumption (min) Power consumption (max)	0.5W 187W
Power Power supply Power consumption standby) Power consumption (min) Power consumption (max) Neight and dimensions	0.5W 187W 225W





Copyright © 2021 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas InstrumentsTM. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 19052021072138