

W400LVe

Bright projection









- Bright WXGA projector 4000 ANSI lumens
- Easy connectivity HDMI, VGA, USB power
- Clear, powerful audio 10W speaker
- · Lightweight and portable

Project bright and vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W400LVe boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.



This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

Specifications

EAN: 5055387664791, Colour: Black

Display/image Display technology DIPTM Resolution WXGA (1280x800) 4,000 lumens Brightness Contrast ratio 25.000:1 Native aspect ratio 16:10 Aspect ratio - compatible 4:3.16:9 Keystone correction - vertical +/-40° 15.38 ~ 91.15Khz Horizontal scan rate 50 ~ 85(120 for 3D)Hz Vertical scan rate Uniformity 75% Screen size 0.82m ~ 7.61m (32.24" ~ 299.53") diagonal

Lamp info Light source type Lamp

Lamp watts 6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+) Lamp life hours (up to)

203

Optical 1.55:1 ~ 1.73:1 Throw ratio Projection distance (m) 1m - 12m Zoom 1.1 Zoom type Manual

Focal length (mm) 21.85 mm~24mm/0.86"~0.945"

Native offset 112%

Connectivity Connections

3D compatibility

Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

x Composite video, 1 x Audio 3.5mm

Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A

Control 1 x RS232

General Noise level (min) 27dB Noise level (max) 29dB

FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:

1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D

Full 3D

Security Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, OSD / display languages

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max Operating conditions

humidity 85%

Remote control Card style Speaker count 10W Watts per speaker AC power cord Remote control In the box

Battery Basic user manual

Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit,

WHD200

Power Power supply 100 ~ 240V, 50 ~ 60Hz

0.5W Power consumption (standby) 187W Power consumption (min) 225W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) mm 316 x 244 x 108 Gross weight 3.58 kg 3.04 kg Net weight





