

## W340

Widescreen, bright and portable









- Bright WXGA projector 3400 ANSI lumens
- Easy connectivity 2x HDMI, MHL, USB Power, 10W speaker
- Low ownership costs up to 10,000 hours<sup>2</sup> lamp life
- Lightweight and portable

Project your presentations in HD effortlessly any time on day with the bright W340. Designed for meeting rooms and classrooms, this small projector boasts high brightness, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



## **Specifications**

Power consumption (max)

mm

Gross weight Net weight

Weight and dimensions Dimensions (W x D x H)

| Specifications                    |   |
|-----------------------------------|---|
| Display/image                     |   |
| Display technology                | DLP   |
| Resolution                        | WXGA (1280x800)   |
| Brightness                        | 3,400 lumens  |
| Contrast ratio                    | 20.000:1  |
| Native aspect ratio               | 16:10   |
| Aspect ratio - compatible         | 4:3,16:9  |
|                                   | +/-40°  |
| Keystone correction -<br>vertical | +/-40   |
| Horizontal scan rate              | 15.3 ~ 91.1Khz  |
| Vertical scan rate                | 24 ~ 85(120 for 3D)Hz   |
| Uniformity                        | 75%   |
| Screen size                       | 0,68m ~ 8,04m (26,87" ~ 316,5") diagonal  |
| Lamp info                         | 0,00m 0,04m (20,07 010,0 ) diagonal   |
| Light source type                 | Lamp  |
| Lamp watts                        | 195   |
| Lamp life hours (up to)           | 5000 (Bright), 7000 (Dynamic), 6000 (Eco), 8000 (Eco+),   |
| ==p ino nouro (up to)             | 10000 (Education)   |
| Lamp life (education)             | 10,000 hours  |
| Optical                           | And a street of the street of |
| Throw ratio                       | 1,55:1 ~ 1,73:1   |
| Projection distance (m)           | 1m - 12m  |
| Zoom                              | 1,1   |
| Zoom type                         | Manual  |
| Focal length (mm)                 | 21.86 ~ 24  |
| Native offset                     | 112%  |
| Connectivity                      |   |
| Connections                       | Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a  |
|                                   | 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1   |
|                                   | x Audio 3.5mm   |
|                                   | Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x   |
|                                   | USB-A power 1A  |
|                                   | Control 1 x RS232   |
| General                           |   |
| Noise level (typical)             | 29dB  |
| Noise level (max)                 | 31dB  |
| PC compatibility                  | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  |
| 2D compatibility                  | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,   |
|                                   | 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,   |
|                                   | 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)   |
| 3D compatibility                  | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:  |
|                                   | 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60   |
| 3D                                | Full 3D   |
| Security                          | Security bar, Kensington Lock, Password protected interface   |
| OSD / display languages           | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,   |
|                                   | Finnish, French, German, Greek, Hungarian, Indonesian,  |
|                                   | Italian, Japanese, Norwegian, Polish, Portuguese, Romanian  |
|                                   | Russian, Chinese (simplified), Spanish, Swedish, Chinese  |
| O                                 | (traditional), Turkish, Vietnamese  |
| Operating conditions              | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m  |
| Remote control                    | Card style  |
| Speaker count                     | 1   |
| Watts per speaker                 | 10W   |
| In the box                        | AC power cord   |
|                                   | Remote control  |
|                                   | Battery<br>Basic user manual  |
| Optional wireless models          | HDCast Pro, QuickCast Bundle, QuickCast starter kit,  |
| optional wireless filodels        | WHD200  |
| Power                             |   |
| Power supply                      | 100 ~ 240V, 50 ~ 60Hz   |
| Power consumption                 | 0.5W  |
| (standby)                         |   |
| Power consumption (min)           | 187W  |
| Power consumption (max)           | 225W  |

225W

3,47 kg

2,17 kg

298 x 230 x 965



