

HZ40ST

Compact high brightness short throw home entertainment laser projector









- Lights on viewing 4200 lumens
- Full HD 1080p laser projector 4K UHD and HDR compatible
- Short throw lens 100" image from just over a metre away
- Easy connectivity 2x HDMI, USB Power and 10W speaker



Feel the action and experience every moment on the big screen with the HZ40ST. Perfect for immersive live sports, TV shows, movies and gaming.

Convenient and easy to set-up, this compact high brightness short throw laser projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on.

Specifications

EAN: 5055387664630, Colour: White

Display/image Display technology

DI P™

Yes

Laser

30.000 hours

Resolution 1080p Full HD (1920x1080)

Brightness 4,200 lumens Contrast ratio 2.500.000:1 Native aspect ratio 16.9 Aspect ratio - compatible 4:3 +/-15° Keystone correction horizontal Keystone correction - vertical +/-15°

Has vertical auto keystone correction

Displayable colours (millions) 1073.4

Horizontal scan rate 15.375 ~ 91.146 Khz 50 ~ 85 Hz (120Hz for 3D)Hz Vertical scan rate

Uniformity 80%

Screen size 0.93m ~ 7.66m (36.43" ~ 301.4") diagonal

Lamp info Light source type LASER life Optical Throw ratio

0.5:1

0.4m - 3.31m Projection distance (m) Zoom type Fixed Focal length (mm) 7.51 Native offset 115%

Connectivity Connections

Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 2 x Audio 3.5mm, 1 x Microphone

Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x micro USB service, 1 x 3D sync

General

3D compatibility

OSD / display languages

Noise level (typical) 30dB Noise level (max) 32dB

UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac PC compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz 2D compatibility

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:

1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface

IP6X IP rating

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese Yes

24/7 operation 360° operation Yes

Operating conditions $5^{\circ}\text{C} \sim 40^{\circ}\text{C}, \, \text{Max. Humidity 85\%, Max. Altitude 3000m}$

Backlit ProAV remote Remote control Speaker count

10W Watts per speaker

In the box AC power cord Remote control 2x AAA batteries

Basic user manual

Input lag

Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit

Networking LAN - control Power

100 ~ 240V, 50 ~ 60Hz Power supply

Power consumption (standby) < 0.5W 206W Power consumption (min) 269W Power consumption (max)

Weight and dimensions Dimensions (W x D x H) mm

337 x 265 x 122.5 Gross weight 6.22 kg 4.5 kg Net weight





