

ZU500USTe

High brightness WUXGA ultra short throw laser projector



- **Bright WUXGA laser projector - 5000 lumens**
- **Ultra short throw lens - Screen Size: 132" 155" (Data) - 132" - 200" (Video)**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Dust resistant - Independently tested, IP5X certification for total reliability**

The ZU500USTe is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a lower total cost of ownership.

Weighing only 5.7kg, this projector can be mounted just centimetres away from a wall or surface.

Supporting 24/7 operation and versatile orientation, the ZU500USTe is a flexible, powerful and bright ultra short throw projector that makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

Specifications

UPC: 796435 44 558 4, EAN: 5055387665385, Colour: white



Display/image	
Display technology	DLP®
Resolution	WUXGA (1920x1200)
Brightness	5,000 lumens
Contrast ratio	100,000:1
Contrast ratio - dynamic	3,000,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	16:9,16:10
Keystone correction - horizontal	10°
Keystone correction - vertical	10°
Uniformity	85%
Screen size	3.35m ~ 3.94m (132" ~ 155") diagonal

Lamp info	
Light source type	Laser
LASER life	30,000 hours

Optical	
Throw ratio	0.253:1
Projection distance (m)	0.727m - 0.84m
Zoom type	Fixed
Focal length (mm)	3.7mm/0.146"
Native offset	117%

Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x Mic 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x USB-B service

General	
Noise level (min)	30dB
Noise level (max)	36dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP5x
OSD / display languages	17 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish
24/7 operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit ProAV remote
Heat dissipation	1,608BTU/hour
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	HDxCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB

Networking	
LAN - control	Yes
LAN	Yes

Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	250W
Power consumption (max)	400W

Weight and dimensions	
Dimensions (W x D x H) mm	383 x 318 x 111
Gross weight	7.8 kg
Net weight	5.8 kg

