

## EH412

High resolution, versatile and powerful









- Bright 1080p projector 4500 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Beam bright, eye catching content with the Full HD 1080p EH412 projector. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.

Additionally, it boasts easy connectivity with multiple inputs including HDMI, VGA and a built in 10W speaker. You can even use the USB Power to connect and power HDMI dongles such as the Google Chromecast.

## **Specifications**

EAN: 5055387663626, Colour: White

Display/image Display technology

DI P™

 Display technology
 DLP™

 Resolution
 1080p Full HD (1920x1080)

 Brightness
 4,500 lumens

 Contrast ratio
 22,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3

 Keystone correction - vertical
 +/-40°

 Horizontal scan rate
 15.38 ~ 91.15 Khz

 Vertical scan rate
 50 ~ 85(120 for 3D)Hz

Uniformity 70%

**Screen size** 0.78m ~ 7.66m (30.8" ~ 301.4") diagonal

Lamp info
Light source type
Lamp watts
240

Lamp life hours (up to) 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Optical Throw rati

 Throw ratio
 1.12:1 ~ 1.47:1

 Projection distance (m)
 1m - 7.5m

 Zoom
 1.3

 Zoom type
 Manual

Focal length (mm) 16.9mm~21.6mm/0.665"~0.85"

Native offset 116%

Connectivity Connections

onnections Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA

(YPbPr/RGB), 1 x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x VGA

Control 1 x RS232

General

3D

Noise level (typical) 26dB Noise level (max) 28dB

PC compatibility UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA,

VGA, Mac

2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

**3D compatibility**Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italia

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

**Operating conditions** 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Data remote with laser and mouse function

Speaker count 1

Watts per speaker 10W

In the box AC power cord

Remote control
2x AAA batteries
Basic user manual

Optional wireless models HDCast Pro, QuickCast Bundle, QuickCast starter kit,

WHD200

Power

**Power supply** 100 ~ 240V, 50 ~ 60Hz

 Power consumption (standby)
 0.5W

 Power consumption (min)
 200W

 Power consumption (max)
 285W

Weight and dimensions

 Dimensions (W x D x H) mm
 316 x 244 x 108

 Gross weight
 3.9 kg

 Net weight
 3.31 kg





