

W515ST

Powerful short throw solution



- **Ultra bright WXGA projector – 5500 ANSI lumens**
- **Short throw lens - 100" image from less than two metres away**
- **Vertical and horizontal lens shift**
- **Four corner geometric projection**

Designed for professional installation environments, the high-specification W515ST short throw projector boasts a brightness of 5500 lumens and is connection ready with two HDMI inputs, MHL compatibility, DisplayPort and multiple analogue and audio connections. Equipped with four corner geometric correction and an impressive lens shift, the flexibility of the W515ST ensures the image is easier to setup and exactly where it is meant to be, even on uneven walls and when projector placement is awkward.

Specifications

EAN: 5055387657786, Colour: White



Display/imagen

Tecnología de visualización	DLP™
Resolución	WXGA (1280x800)
Brillo	5.500 lúmenes
Brillo ANSI	5.500 lúmenes
Ratio de contraste	10.000:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3,16:9
Corrección Keystone - Horizontal	+/-30°
Corrección Keystone- Vertical	+/-30°
Corrección Keystone vertical automática	Yes
Reproducción de color (millones)	1073.4
Frecuencia de muestreo horizontal	15.375 ~ 91.146Khz
Frecuencia de muestreo vertical	24 ~ 85(120 for 3D)Hz
Uniformidad	80%
Tamaño de pantalla	0.71m ~ 7.67m (27.97" ~ 302") diagonal

Info Lámpara

Fuente de luz	Lámpara
Vatios lámpara	365
Vida de lámpara (horas)	3000 (Bright), 5000 (Eco+)

Óptica

Distancia de tiro	0.83:1
Distancia de proyección (m)	0.5m - 5.4m
Tipo de zoom	Fija
Distancia focal (mm)	11.66
Lenshift	Vertical +20%, Horizontal +10%
Offset nativo	105%

Conectividad

Conexiones	Inputs 1 x HDMI 1.4a / 3D + MHL, 1 x HDMI 1.4a / 3D , 1 x DisplayPort, 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x S-Video, 1 x Audio RCA L&R, 2 x Audio 3.5mm, 1 x Mic 3.5mm Outputs 1 x VGA (YPbPr/RGB), 1 x Sincronización 3D, 1 x Alimentación USB-A 1.5A, 1 x 12V trigger, 1 x Remoto por cable, 1 x Audio 3.5mm Control 1 x RS232, 1 x Mini USB ratón/servicio
------------	---

General

Nivel sonoro (típico)	28dB
Nivel sonoro (max)	30dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	Full 3D
Seguridad	Security bar, Kensington Lock, Password protected interface
Idiomas OSD / display	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operatividad 24/7	Yes
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Mando ProAV retroiluminado
Altavoces	2
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control, 2x AAA batteries Basic user manual
Modelos inalámbricos opcionales	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200

Networking

LAN - control	Yes
---------------	-----

Corriente

Fuente de alimentación	100V ~ 240V ± 10%, 50-60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	340W
Consumo energético (máx.)	425W

Peso y dimensiones

Dimensiones (ancho x profundidad x alto)	424 x 344 x 160
Peso bruto	8.4 kg
Peso neto	6.1 kg



Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 01102023072735