

ZU500USTe

High brightness WUXGA ultra short throw laser projector



- **Bright WUXGA laser projector - 5000 lumens**
- **Ultra short throw lens - Screen Size: 132" 155" (Data) - 132" - 200" (Video)**
- **DuraCore laser technology - 30,000 hours maintenance-free laser light source**
- **Dust resistant - Independently tested, IP5X certification for total reliability**

The ZU500USTe is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a lower total cost of ownership.

Weighing only 5.7kg, this projector can be mounted just centimetres away from a wall or surface.

Supporting 24/7 operation and versatile orientation, the ZU500USTe is a flexible, powerful and bright ultra short throw projector that makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

Specifications

UPC: 796435 44 558 4, EAN: 5055387665385, Colour: white



| | |
|----------------------------------|---|
| Display/image | |
| Display technology | DLP™ |
| Resolution | WUXGA (1920x1200) |
| Brightness | 5,000 lumens |
| Contrast ratio | 100,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 16:9,16:10 |
| Keystone correction - horizontal | 10° |
| Keystone correction - vertical | 10° |
| Uniformity | 85% |
| Screen size | 3.35m ~ 3.94m (132" ~ 155") diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 0.253:1 |
| Projection distance (m) | 0.727m - 0.84m |
| Zoom type | Fixed |
| Focal length (mm) | 3.7mm/0.146" |
| Native offset | 117% |
| Connectivity | |
| Connections | Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x Mic 3.5mm Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x USB-B service |
| General | |
| Noise level (min) | 30dB |
| Noise level (max) | 36dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP5x |
| OSD / display languages | 17 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish |
| 24/7 operation | Yes |
| Operating conditions | 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% |
| Remote control | Backlit ProAV remote |
| Heat dissipation | 1,608BTU/hour |
| Speaker count | 1 |
| Watts per speaker | 10W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200, WUSB |
| Networking | |
| LAN - control | Yes |
| LAN | Yes |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 250W |
| Power consumption (max) | 400W |
| Weight and dimensions | |
| Dimensions (W x D x H) mm | 383 x 318 x 111 |
| Gross weight | 7.8 kg |
| Net weight | 5.8 kg |

