

HD29HLVx

Big screen gaming and sports anytime of day





- Lights on viewing 4500 lumens for use any time of day
- 4K UHD and HDR compatible Enhanced detail for an immersive viewing experience
- Lightning fast gaming projector Supports 1080p 120Hz with 8.4ms response time
- Easy connectivity 2x HDMI, USB power and built-in 10W speaker



Feel the action with the high brightness HD29HLVx. Experience every moment on the big screen for immersive gaming, live sports and movies.

Convenient and easy to set up, this compact high brightness projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on. Boasting HDR and Amazing colour technology, it delivers accurate true-to-life colour reproduction for movie lovers. It also supports 1080p 120Hz for low input latency of 8.4ms – perfect for games that rely on rapid reactions.

Specifications

EAN: 5055387666429, Colour: Whi	ite
Display/image	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	4,500 lumens
Contrast ratio	50,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
	+
Keystone correction - vertical	
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	70%
Screen size	0.78m ~ 7.66m (30.8" ~ 301.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.12:1 ~ 1.47:1
Projection distance (m)	1m - 7.5m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	16.9 ~ 21.6
Native offset	116%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x RS232
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA,
r o compatibility	VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
	Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
	Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
	Chinese (simplified), Spanish, Swedish, Chinese (traditional),
	Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord
	Remote control
	2x AAA batteries
	Basic user manual
Optional wireless models	WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	200W
	285W
Power consumption (max)	20011
Weight and dimensions	316 x 244 x 108
Weight and dimensions Dimensions (W x D x H) mm	316 x 244 x 108
Power consumption (max) Weight and dimensions Dimensions (W x D x H) mm Gross weight Net weight	316 x 244 x 108 3.88 kg 3.3 kg





Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 25082023060403