

ZH400UST

Superb for signage - 20,000 hours full brightness**



© Samruh Creative Association

- **Bright Full HD 1080p laser projector - 4000 ANSI Lumens**
- **Ultra short throw lens - 100" image from less than half a metre away**
- **20,000 hours maintenance-free laser light source at full brightness****
- **Dust resistant – Independently tested, IP5X certification for total reliability**

The ZH400UST is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a low total cost of ownership.

Weighing only 5.6kg, this projector can be mounted just centimetres away from a wall or surface and can project an image size of over 100 inches (254cm).

Supporting 24/7 operation and versatile orientation, the ZH400UST is a flexible, powerful and bright ultra short throw projector which makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

Specifications

Display/imagen	
Tecnología de visualización	DLP
Resolución	1080p Full HD (1920x1080)
Brillo	4.000 lumens
Ratio de contraste	100.000:1
Relación de aspecto nativo	16:9
Ratio de aspecto - compatible	4:3
Corrección Keystone-Vertical	+/-15°
Frecuencia de muestreo horizontal	15.3 ~ 91.1Khz
Frecuencia de muestreo vertical	24 ~ 85(120 for 3D)Hz
Uniformidad	80%
Tamaño de pantalla	2.21m ~ 2.59m (87" ~ 102") (diagonal)
Info Lámpara	
Fuente de luz	Laser
Vida del LÁSER	30.000horas
Óptica	
Distancia de tiro	0.25:1
Distancia de proyección (m)	0.45m - 0.59m
Tipo de zoom	Fija
Distancia focal (mm)	3.72
Offset nativo	120%
Conectividad	
Conexiones	Inputs 2 x HDMI 1.4a / 3D , 2 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm, 1 x Audio RCA L&R Outputs 1 x VGA compartida con VGA2, 1 x Audio 3.5mm, 1 x USB-A power 2A Control 1 x RS232, 1 x RJ45, 1 x mini USB servicio, 1 x USB-A wireless
General	
Nivel sonoro (típico)	30dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Seguridad	Security bar, Kensington Lock, Password protected interface
idiomas OSD / display	18 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional), Turkish
Condiciones de funcionamiento	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Control remoto	Si
Altavoces	1
Wattios por altavoz	10W
Contenido caja	AC power cord Remote control 2x AAA batteries Basic user manual
Networking	
LAN - control	Yes
Corriente	
Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético (mín.)	210W
Consumo energético (máx.)	330W
Peso y dimensiones	
Peso	5.6kg
Dimensiones (W x D x H)	382 x 310 x 124

