

4K550

Gerçeğe yakın ayrıntılar - 4K Ultra HD projektör



© Samruh Creative Association

- **HDR10 ile 4K UHD çözünürlük**
- **Parlak 5000 Lumen**
- **1.6 x zoom**
- **%15 dikey lens kaydırma**

Yüksek parlaklıkta Ultra HD'nin avantajlarını projeksiyon kurulumunuza getirin. Optoma 4K550, inanılmaz bir 5000 lümenle etkileyici 4K UHD görüntüler sunar. Bu üst düzey teknik özellikler, gerçeğe yakın renk çoğaltma özellikleriyle birlikte her türlü sunuma hayat ve netlik getirir.



Specifications

EAN: 5055387660908, Colour: White



Display/image	
Display technology	DLP™
Resolution	UHD (3840x2160)
Brightness	5,000 lumens
Brightness (eco)	3,000 lumens
ANSI brightness	5,000
Contrast ratio	10,000:1
Contrast ratio - dynamic	6,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.67m ~ 7.68m (26.45" ~ 302.2") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	330
Lamp life hours (up to)	3000 (Bright), 5000 (Dynamic), 4000 (Eco), 5000 (Eco+)
Optical	
Throw ratio	1.39:1 ~ 2.22:1
Projection distance (m)	1.3m - 9.3m
Zoom	1.6
Zoom type	Manual
Focal length (mm)	20.91mm~32.62mm/0.823"~1.284"
Lens shift	Vertical +15%
Native offset	100%
Lens shift	Yes - {{downloads_link}}
Connectivity	
Connections	Inputs 1 x HDMI, 1 x HDMI/MHL, 1 x VGA, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x USB-A power 1.5A, 1 x USB-A service, 1 x RJ45, 1 x 12V trigger, 1 x RS232 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 2 x Speaker
General	
Noise level (typical)	32dB
Noise level (max)	34dB
PC compatibility	UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz)
3D compatibility	120Hz Frame Sequential (Max. 1920x1080 120Hz, PC only)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Data remote with laser and mouse function
Speaker count	2
Watts per speaker	5W
In the box	AC güç kablosu Uzaktan kumanda 2 adet AAA pil Hızlı başlangıç Kılavuzu
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	249W
Power consumption (max)	335W
Weight and dimensions	
Dimensions (W x D x H) mm	392 x 281 x 129
Gross weight	7.14 kg
Net weight	6.07 kg

