

# ZU506

High brightness professional laser projector



© Samruh Creative Association

- **Bright WUXGA laser projector - 5000 ANSI Lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **IP5X Dust protection**
- **4K, HDR Compatible**



Professional life like colours and a smaller lighter chassis than ever before. 4K and HDR compatible, the ZU506 is a low maintenance projector with extremely long-life laser technology at an impressive 5000lms.

## Specifications

EAN: 5055387662551, Colour: White

EAN: 5055387662896, Colour: Black



### Display/image

|                                       |                                       |
|---------------------------------------|---------------------------------------|
| Display technology                    | DLP™                                  |
| Resolution                            | WUXGA (1920x1200)                     |
| Brightness                            | 5,000 lumens                          |
| ANSI brightness                       | 5,000                                 |
| Contrast ratio                        | 300,000:1                             |
| Native aspect ratio                   | 16:10                                 |
| Aspect ratio - compatible             | 4:3,16:9,16:10                        |
| Keystone correction - horizontal      | +/-30°                                |
| Keystone correction - vertical        | +/-30°                                |
| Has vertical auto keystone correction | Yes                                   |
| Displayable colours (millions)        | 1073.4                                |
| Horizontal scan rate                  | 15.375 ~ 91.146 KHz                   |
| Vertical scan rate                    | 50 ~ 85 Hz (120Hz for 3D)Hz           |
| Uniformity                            | 85%                                   |
| Screen size                           | 0.74m ~ 7.62m (29.1" ~ 300") diagonal |

### Lamp info

|                   |              |
|-------------------|--------------|
| Light source type | Laser        |
| LASER life        | 30,000 hours |

### Optical

|                         |  |
|-------------------------|--|
| Throw ratio             | 1.4:1 ~ 2.24:1                           |
| Projection distance (m) | 1m - 10m                                 |
| Zoom                    | 1.6                                      |
| Zoom type               | Manual                                   |
| Focal length (mm)       | 20.91 ~ 32.62                            |
| Lens shift              | Vertical -99 ~ 107%                      |
| Native offset           | 99%                                      |
| Lens shift              | Yes - <a href="#">{{downloads_link}}</a> |

### Connectivity

|             |  |
|-------------|--|
| Connections | <b>Inputs</b> 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x RS232, 1 x Mic 3.5mm, 1 x Audio 3.5mm, 1 x RJ45<br><b>Outputs</b> 1 x VGA, 1 x USB-A power 1.5A, 1 x Audio 3.5mm |
|-------------|--|

### General

|                          |  |
|--------------------------|--|
| Noise level (typical)    | 28dB   |
| Noise level (max)        | 33dB   |
| PC compatibility         | UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  |
| 2D compatibility         | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  |
| 3D compatibility         | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D   |
| 3D                       | Full 3D  |
| Security                 | Security bar, Kensington Lock, Password protected interface  |
| IP rating                | IP5X   |
| OSD / display languages  | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 24/7 operation           | Yes  |
| 360° operation           | Yes  |
| Operating conditions     | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m   |
| Remote control           | Backlit ProAV remote   |
| Speaker count            | 2  |
| Watts per speaker        | 10W  |
| In the box               | AC power cord<br>Remote control<br>2x AAA batteries<br>Basic user manual   |
| Optional wireless models | HDCast Pro, QuickCast Bundle, QuickCast starter kit  |

### Networking

|               |     |
|---------------|-----|
| LAN - control | Yes |
|---------------|-----|

### Power

|                             |                      |
|-----------------------------|----------------------|
| Power supply                | 100V ~ 240V, 50-60Hz |
| Power consumption (standby) | <0.5W                |
| Power consumption (min)     | 190W                 |
| Power consumption (max)     | 341W                 |

### Weight and dimensions

|                           |                 |
|---------------------------|-----------------|
| Dimensions (W x D x H) mm | 374 x 302 x 117 |
| Gross weight              | 7.8 kg          |
| Net weight                | 5.5 kg          |

