

X402

Bright, powerful and business ready



- **Bright XGA projector – 4200 ANSI lumens**
- **Crestron RoomView® – RJ45 control and monitoring**
- **Easy connectivity – HDMI, VGA and built-in 10W speaker**
- **Lightweight and portable - Carry bag included**



Project bright vibrant widescreen presentations any time of day. Designed for meeting rooms and classrooms, the X402 boasts a long lamp life and energy-saving features which provide a low overall cost of ownership.

This projector has a built-in speaker, networking capabilities, Full 3D technology and HDMI connectivity. It is also lightweight so can be installed or taken on the move in the handy carry bag for off-site meetings.

Specifications

EAN: 5055387600157, Colour: White

Display/image	
Display technology	DLP™
Resolution	XGA (1024x768)
Brightness	4,200 lumens
Contrast ratio	20,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-0°
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.78m ~ 7.8m (30.8" ~ 307") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	260
Lamp life hours (up to)	3000 (Bright), 5500 (Dynamic), 5000 (Eco), 7000 (Eco+)
Optical	
Throw ratio	1.6:1 ~ 1.92:1
Projection distance (m)	1.2m - 12m
Zoom	1.2
Zoom type	Manual
Focal length (mm)	18.2 ~ 21.9
Native offset	115%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x VGA (YPbPr/RGB), 1 x Composite video, 2 x Audio 3.5mm Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Control 1 x RS232, 1 x RJ45, 1 x 3D sync, 1 x mini USB mouse/service
General	
Noise level (typical)	31dB
Noise level (max)	33dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
3D	
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	20 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	Carry bag AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	QuickCast Bundle, QuickCast starter kit, WHD200
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	257W
Power consumption (max)	306W
Weight and dimensions	
Dimensions (W x D x H) mm	315 x 224 x 102
Gross weight	4.1 kg
Net weight	2.57 kg

