

EH416e

Compact and powerful Full HD 1080p projector



- **Bright Full HD 1080p projector – 4200 ANSI lumens**
- **Installation flexibility – Vertical lens shift and 1.6x zoom**
- **Ultimate control - Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - HDMI, MHL, VGA, 10W speaker**



Project high resolution visuals regardless of the ambient light level using the bright full HD 1080p EH416. Designed for businesses and professional installation environments this compact and powerful projector can be installed or taken on the move. Perfect for small edge blending and stacking projects.

Easy to connect to with multiple inputs including two HDMI, MHL, VGA and a built in 10W speaker. You can even present wirelessly using the HDCast Pro (sold separately) or use the USB Power to connect and power HDMI dongles such as the Google Chromecast.

Specifications

EAN: 5055387664784, Colour: White

Ekrana ve görüntü	
Görüntü Teknolojisi	DLP™
Doğal Çözünürlük	1080p Full HD (1920x1080)
Parlaklık (Lümen)	4.200
Kontrast Oranı	20.000
Doğal en boy oranı	16:9
Desteklenen en-boy oranı	4:3
Keystone Düzeltme (Dikey)	+/-40°
Yatay Tarama Hızı (Hz)	15 ~ 91
Dikey Tarama Hızı (Hz)	24 ~ 85(120 for 3D)
Uniformity (Yüzde)	80
Ekrana boyutu	0.67m ~ 7.7m (26.21" ~ 303.3") diagonal
Lamba bilgisi	
Işık Kaynağı	Lamba
Lamba (Watt)	240
Lamba ömrü saatleri (en fazla)	4000 (Bright), 8000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optik	
Atma oranı	1.4:1 ~ 2.24:1
ProjeksiyonMesafeMetre	1.3m - 9.4m
SabitLensZoom	1.6
SabitLensZoomType	Manual
SabitLensOdak Uzunluğu	20.91 ~ 32.62
SabitLensShift	Vertical +17%
Doğal offset	99%
bağlantı	
Bağlantılar	Inputs 1 x HDMI 1.4a 3D desteği + MHL, 1 x HDMI 1.4a 3D desteği, 1 x VGA (YPbPr / RGB), 1 x Kompozit video, 2 x Ses 3,5 mm Outputs 1 x VGA (YPbPr / RGB), 1 x Ses 3,5 mm, 1 x USB-A gücü 1A Control 1 x RS232, 1 x RJ45, 1 x mini USB mouse / servis
Genel	
Gürültü Düzeyi Tipik (Db)	32
Gürültü Seviyesi Max (Db)	34
Bilgisayar Uyumluluğu	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D Uyumluluk	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D Uyumluluk	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
Proj3DType	Full 3D
Ürün Güvenliği	Security bar, Kensington Lock, Password protected interface
OSDLang'lar	21 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish
Çalışma koşulları	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Uzaktan kumanda	Lazer ve fare işlevli uzaktan kumanda
Hoparlör Sayısı	1
Hoparlör Watt	10
Kutuda	AC power cord Remote control 2x AAA batteries Basic user manual
İsteğe bağlı kablosuz modeller	HDcast Pro, QuickCast Bundle, QuickCast starter kit, WHD200
ağ	
LanControl	Yes
Güç	
Güç kaynağı	100 ~ 240V, 50 ~ 60Hz
Güç Tüketimi / Watt (Beklemede)	0.5
Güç Tüketimi / Watt (Min)	249
Güç Tüketimi / Watt (Maks)	309
Ağırlık ve boyutlar	
Ürün Boyutları	315 x 224 x 114
Brüt ağırlık	3.8 kg
Net ağırlığı	3.23 kg

